

EDGE

EDGE GEO

 Part **EDESGE**

The EDGE GEO is built for accurate temperature and humidity monitoring combined with Geo location tracking. It is ideal for moving assets, storage spaces, and commercial environments. With every direct-to-cloud cellular upload, the device automatically sends its current Geo location so you always know where your data is coming from.



At a glance



MEASURES
 Ambient Temperature, Relative Humidity, Digital Input



CONNECTIVITY
 WiFi 2.4 GHz · LTE-M / NB-IoT · Bluetooth LE



BATTERY LIFE
 Up to 2 years on 4 × AA



INTERNAL MEMORY
 49,000 records of each measured parameter



RECORDING INTERVAL
 1 to 30 minutes



INGRESS PROTECTION
 IP31

Ports and connectivity

Port I

Not used

Port II

Dry Contact / Flood

Port III

Not used

Connectivity

WiFi 2.4 GHz · LTE-M / NB-IoT · Bluetooth LE

Built-in sensors

SENSOR	RANGE	ACCURACY	RESOLUTION
Ambient Temperature Built-in · Record & Alarm	-20 °C to +70 °C (-4 °F to +158 °F)	±0.2 °C (±0.36 °F)	0.1 °C (0.2 °F)
Relative Humidity Built-in · Record & Alarm	0% to 99% non-condensing	±3% RH (Sensirion SHT40)	1%

Plug-in sensors

SENSOR	CABLE
Digital Input (Dry Contact / Flood) Detachable · Optional · Alarm	Up to 100 m (330 ft)

RECORDING, LF CLOUD AND POWER

Internal memory	49,000 records of each measured parameter
Recording interval	1 to 30 minutes
Cloud sync interval	10 minutes to 7 days (alarms are sent immediately, whatever the interval)
Battery life	Up to 2 years on 4 × AA (depending on settings, reception, ambient temperature, battery quality, alarms, buzzer and BLE)
External power	USB-C 5 V DC (supply not included)

ENCLOSURE AND ENVIRONMENT

Dimensions (L × W × H)	104 × 88 × 30 mm (4 3/32 × 3 15/32 × 1 3/16 in)
------------------------	---

Net weight	233 g (8.2 oz)
Display update range	0 to +50 °C (32 to 122 °F)
Ingress protection	IP31 (housing, protected against dripping water, not waterproof)

WIRELESS AND COMPLIANCE

Compliance	FCC, IEEE 802.11 b/g, NIST traceable, RoHS, CE (EN 61326-1 and EN 61010-1, 3rd edition)
WiFi	IEEE 802.11 b/g/n, 2.4 GHz · Contains FCC ID 2AC7Z-ESPWROOM32
Cellular	LTE with 3G/2G fallback (built-in global eSIM) · Contains FCC ID 2AJYU-8VC0001

Request a quote →

Sold and supported through LoggerFlex distributors. An engineer replies within one business day.

sales@loggerflex.com 1-888-365-8880 www.loggerflex.com/en/product/edge-geo



Product page,
manuals and
LF Cloud
setup