

EDGE

EDGE Plus WiFi

Part **EDWIPL**

The EDGE PLUS is designed for precise ambient temperature and humidity monitoring in preservation-sensitive environments such as museums, archives, storage areas, offices, server rooms, and residential or commercial buildings. Featuring a fixed (not detachable), water-resistant temperature and RH probe (Sensirion SHT45) on a 1 m (3.3 ft) cable, with no built-in temperature or humidity sensor, it allows accurate measurements directly at the point of concern while keeping the main device safely mounted away from harsh conditions.



At a glance



MEASURES

Power-loss alarm, Temperature Probe, T/RH probe



CONNECTIVITY

WiFi 2.4 GHz · Bluetooth LE



BATTERY LIFE

Up to 3 years on 4 × AA



INTERNAL MEMORY

49,000 records of each measured parameter



RECORDING INTERVAL

1 to 30 minutes



INGRESS PROTECTION

IP31

Ports and connectivity

Port I

Temperature Probe

Port II

Temperature & RH Probe

Port III

Temperature Probe

Connectivity

WiFi 2.4 GHz · Bluetooth LE

Built-in sensors

SENSOR

Power-loss alarm (USB-C)

Built-in · Alarm

— Plug-in sensors

SENSOR	RANGE	ACCURACY	RESOLUTION	CABLE
Temperature Probe (DS18B20, optional) Detachable · Optional · Record & Alarm	-55 °C to +125 °C (-67 °F to +257 °F)	±0.5 °C (±0.9 °F) from -10 to +85 °C (+14 to +185 °F); ±2 °C (±3.6 °F) at -55 °C / +125 °C (-67 °F / +257 °F)	0.1 °C (0.2 °F)	1.5 m (4.9 ft)
T/RH probe (Sensirion SHT45, fixed) Fixed · Included · Record & Alarm	0% RH - -40 °C to 99% RH - +125 °C (-40 °F to +257 °F)	±0.1 °C (±0.2 °F) and ±1.0% RH typical	0.1 °C (0.2 °F), 1% RH	1 m (3.3 ft)

RECORDING, LF CLOUD AND POWER

Internal memory	49,000 records of each measured parameter
Recording interval	1 to 30 minutes
Cloud sync interval	10 minutes to 7 days (alarms are sent immediately, whatever the interval)
Battery life	Up to 3 years on 4 × AA (depending on settings, reception, ambient temperature, battery quality, alarms, buzzer and BLE)
External power	USB-C 5 V DC (supply not included)

ENCLOSURE AND ENVIRONMENT

Dimensions (L × W × H)	104 × 88 × 30 mm (4 3/32 × 3 15/32 × 1 3/16 in)
Net weight	283 g (10.0 oz)

Operating temperature	-20 °C (-4 °F) to +70 °C (+158 °F)
Display update range	0 °C (32 °F) to +50 °C (122 °F)
Ingress protection	IP31 (housing, protected against dripping water, not waterproof)
Probe extension	Up to 16.5 m (54 ft) in total, including the 1.5 m (4.9 ft) probe lead: up to five 3 m (10 ft) AUDEX3 extensions; keep two probe runs within 3 m (10 ft) of each other

WIRELESS AND COMPLIANCE

Compliance	FCC, IEEE 802.11 b/g, NIST traceable, RoHS, CE (EN 61326-1 and EN 61010-1, 3rd edition)
WiFi	IEEE 802.11 b/g/n, 2.4 GHz · Contains FCC ID 2AC7Z-ESPWROOM32

— Good to know

RH sensor pocket is water resistant

Request a quote →

Sold and supported through LoggerFlex distributors. An engineer replies within one business day.

sales@loggerflex.com 1-888-365-8880 www.loggerflex.com/en/product/edge-essential-wifi-plus



Product page,
manuals and
LF Cloud
setup